DATA SHEET | 2021








Full Spectrum RGBW Color Change SMX93



| PART DESCRIPTION | FULL SPECTRUM RGBW SMX93 SURFACE MOUNT UNDERWATER LED LIGHT |
|-------------------------|---|
| Part Number | 60-0315 |
| Available Colors | Full Spectrum RGBW Color Change |
| Lumens | 11,475 |
| Fixture Lumens (White) | 5,100 |
| Number & Type Of LED | White-12×5W / Green-12×3W / Blue-12×3W / Red-16×3W |
| LED Power - HICOB Array | Yes |
| Typical LED Life | 50,000+ Hours |
| Warranty | 2 Years |
| User Control Options | On/Off Switch (Third party supplied) |
| Electrical Installation | Simple 2 Wire Connection |
| Housing Type | Marine Bronze Body with Borosilicate Glass Lens |
| Compact Size | Diameter: 70mm (2.75") Height: 17mm (0.67") |







DATA SHEET | 2021



Full Spectrum RGBW Color Change SMX93



| TECHNICAL | |
|--|--|
| Driver | Multi-Channel Internal Driver |
| Supply Voltage Range | 10.5–31 V DC |
| Max Current Draw 12/24V | 3.0 A/1.5 A |
| Surge Protection | Yes (3,000V) |
| ATRB (Automatic Thermal Roll- Back) | Yes |
| Low Voltage Protection | Automatic Voltage Roll-Back Control And Low Voltage Cut Out |
| Auto Power Control | Yes – Intelligent Multi-Channel Power Management |
| "Soft Start" Electronics Protec- tion | Yes |
| Reverse Polarity Protection | Yes |
| In Rush Current Protection | Yes |
| Power Line Noise Suppression | Yes |
| Bonding | Not Required |
| Electrical Installation | Simple 2 Wire Connection |
| Max Vessel Length | 7.5m (25') |
| Hull Material Type | All (Isolation Kit Must Be Used On Con- ductive Hull Materials) |

| PHYSICAL | |
|--|--|
| Beam Angle | 90° |
| Water Ingress Protection Rating | IP68 |
| Light Face Diameter | 70mm (2.75") |
| Profile (Height) Of Housing | 17mm (0.67") |
| Housing Type | Marine Bronze Body with Borosilicate Glass Lens |
| Light Cable Length | 2m (6'6'') Standard (Can be extended *) |
| Hole Cut-Out for Cable (Drill bit size) | Metric: 13.5mm Imperial: 17/32" (0.5313") |
| Weight | 435g (0.95 Lbs) |
| Mechanical Installation | 3 x Marine Bronze Screws (Provided) |

* Extension distance depends on cable type, refer to user manual for further information

| LIGHTING SYSTEM FUNCTIONALITY (ON/OFF SWITCH) | | |
|--|-----|--|
| Full Color Spectrum Color Cycle | Yes | |
| Select Color (toggle on/off switch to pause color cycle) | Yes | |
| | | |

| ACCESSORIES | PART NUMBER |
|---------------------------------|-------------|
| SMX M Series Hull Isolation Kit | 39-0203 |

DATA IS SUBJECT TO CHANGE WITHOUT NOTICE

LUMISHORE DATASHEET