



PowerBrick

Lithium-Ion battery

Smart



12V battery pack - Lithium Iron-Phosphate (LiFePO₄) - 150Ah

- **High lifespan:** 3000 cycles and more (see chart)
- **Cell heating system for negative-temperature operation:**
- **Remote monitoring by Bluetooth** (SOC, cell voltage, SOH, etc.)
- **Deep discharge** allowed up to 100 %
- Ultra safe **Lithium Iron Phosphate** chemistry (no thermal run-away, no fire or explosion risks)
- **Embedded BMS** (Battery Management System) : **improve lifespan AND secure the battery**
- No **Lead**, no **rare earths**, no **acid**, no **degassing**
- Calendar life > **10 years**
- **Flexible deployment** : up to 16 packs in parallel and 4 in series
- **Constant power** during discharge (very low internal resistance)
- **Very low Peukert's losses** (energy efficiency >98 %)
- **Very low self discharge** (<3 % per month)
- **No memory effect**
- About **50 % lighter** and **40% smaller** than equivalent Lead-AGM battery with same usable energy
- **Certification** : CE, RoHS, UN-38.3, UN-62619 for cell

Technical Specifications

Electric	Nominal voltage / Nominal capacity	12.8V / 150Ah
	Stored energy	1920 Wh
	Volumetric energy density / Specific energy	176.6 Wh/L / 121.5 Wh/Kg
	Internal resistance	≤ 50mΩ
	Cycles	>3000 cycles (see chart)
	Self discharge	< 3 % per month
	Energy efficiency	> 98%
Standard Charge	Charge voltage	14.4V ± 0.2V (Optional floating voltage : 13.36V max)
	Charge mode	CC/CV : Constant Current / Constant Voltage
	Continuous charge current / Maximum charge current	75 A / 150 A
	BMS charge cut-off voltage	14.8V ± 0.1V
Standard Discharge	Instant peak discharge current	650 A ±50 A (max 150ms)
	Continuous discharge current	150 A (1.92 kW)
	Maximum discharge current (< 30s)	250 A (3.2 kW))
	BMS discharge cut-off voltage	10 V
Environment	Charge temperature range	0°C to +60°C
	Discharge temperature range	-20°C to +60°C
	Storage temperature	0°C o +50°C @60±25% relative humidity
	IP protection level	IP 65
Mechanical	Type of cells	Cylindrical
	Casing material	ABS
	Dimensions	L : 307mm x P : 167mm x H : 212 mm
	Weight	15.8 kg
	Terminal	M8 bolt



APPLICATIONS

- **Electrical vehicules and utilities**
- **Robotics and AGVs**
- **Solar and wind energy storage**
- **Marine**
- **Street lightning**
- **CCTV and security camera**
- **UPS, electric back-up**
- **Telecom**
- **Medical equipments**
- ...



PowerBrick
Lithium-Ion battery


Smart

SHIP
CONTROL




Charts and curves


Different Rate Discharge Curve @25°C




Discharge Curves (0.5C) at different Temperatures




State of Charge Curve @0.5C 25°C




Charging Characteristics @0.5C 25°C






Number of cycles vs. Depth of discharge (DoD)



Different Temperature Self Discharge Curve



Dimensions



 Cold Weather
Compatible

 **Bluetooth**
SMART

Ship Control Srl

Via dei Ghivizzani 1743/B
55054 Piano di Mommio (LU)
P.IVA/C.F.: 04302910759

tel. +39.0584.1660878
cell. +39.345.5625353
www.shipcontrolstore.it
info@shipcontrol.it
info@pec.shipcontrol.it